



technical data sheet.



naked concrete

industrial Look

bring out the natural color of raw material from your building.

strong and **durable** with high **scratch resistance**

naked concrete

description.

Instant mortar with homogeneous and consistent material composition that functions as filling & painting in one application stage on various surfaces (concrete, old plaster, paint, plastering walls, cement board, gypsum board and old ceramics)

color options.

- cement white
- white sand

features & benefits.

- thickness 3 mm
- bonded well with various surfaces (light brick, concrete, old plaster, paint, stucco walls, cement board, gypsum board and old ceramics)
- no hair crack due to shrinkage and Resistant to friction
- smooth & dust-free surface
- natural exposed cement colors options

finish options.

- matte
- satin

technical informations.

crack resistance	: high
concrete strength	: k500
scratch resistance	: high
limitation	: no grout no size limitation
reference standard	: DIN 18550
water requirement	: 6.0 - 7.0 liter / 20 kg
spreadability	: ± 4 m ² / 20 kg / 3 mm
application thickness	: ± 3 mm
pot age	: 2 hours @35OC
adhesion	: 0.45 - 0.80 N/mm ² EN 1015 - 12
comprehensive strength	: 16.99 - 17.00 N/mm ² @28 days DIN 18555 part 3

optional add-on.

- anti stain